TECHNICAL DATASHEET

PANASEAL - POSITIVE PRESSURE FACEMASK FOR SCBA



DESCRIPTION

The Scott Panaseal facemask is available in 2 different sizes and will accommodate a wide range of facial shapes and sizes. The masks are positive pressure and feature a Neoprene outer mask with reflex seal and Neoprene ori-nasal inner mask.

The facepiece visor is single curvature and made of a scratch and impact resistant polycarbonate material with a flame-retardant coating and provides excellent panoramic vision. The visor is held in place by two U-shaped clamps.

The mask will allow the wearer to wear integrated spectacle frames, without compromising the facemask seal. The mask is available with either a five-point fully adjustable neoprene strap style harness or a two-point adjustable Polyester or $Kevlar^{TM}$ net style harness.

The facemask features a left hand side bayonet connection for the demand valve. An option of an additional right quick-fit port to take a communications interface is also available.

A speech diaphragm is mounted at the front of the mask to offer unimpeded speech transmission and there is a low resistance positive pressure exhalation valve that allows for normal breathing with no extra effort. The mask is designed with separate inspiratory and expiratory paths to minimize the risk of cross contamination of second stage regulators.

APPLICATIONS

The Panaseal is specifically designed for use with the Scott range of breathing apparatus from the Professional Fire Fighting SCBA through to the Airline and Escape breathing apparatus range. In conjunction with Scott breathing apparatus it is suitable for providing respiratory protection in an IDLH environment.



TECHNICAL DATASHEET

APPROVALS

CE marked in accordance with EN136 Class III

CE marked in accordance with EN137:2006 Class II when used in conjunction with Scott Propak

CE marked in accordance with EN139 when used with Scott airline equipment AS1716

AS/NZ 1716

| TECHNICAL SPECIFICATIONS | |
|--------------------------|--|
| MATERIALS | |
| Outer Mask | Neoprene |
| Inner mask | Neoprene |
| Head harness | 5 point rubber, net head harness in polyester or Kevlar material |
| Inhale valve flaps | Silicone |
| Exhale valve flaps | Polyisoprene rubber |
| Visor | Polycarbonate with anti scratch coating |
| Exhale valve housing | Polyamide |
| Exhale valve spring | Stainless Steel |
| Screws | Stainless Steel |
| Buckles | Polyamide |
| Demand Valve Port | Glass filled polyamide |
| Packing specification | 23x17x13cm 1kg |

www.norrscope.com

