

SPECIFICATIONS

PROPAK - SIGMA - SELF CONTAINED BREATHING APPARA-

MATERIALS	
Pressure Reducing Valve	Nickel Plated Brass
Rust Tube (Cyls)	Brass
Reducing Valve Seat	Polyamide (Nylon)
O-Rings	Nitrile, Silicone, EPDM
Reducing Valve Springs	Stainless Steel
HP Pressure Gauge	Stainless Steel, Polycarbonate Lens
HP Pressure Gauge Cover	Neoprene
MP Air Supply Hose Fittings	Nickel Plated Brass
Facemask	Neoprene, Silicone or Procomp
Facemask Visor	Polycarbonate
MP Air Supply Hose	EPDM Cover, fabric braid reinforcement, EPDM liner
HP Air Hose	PTCFE liner, stainless steel braiding, Estane sleeve
Valve Handwheel (Cyls)	Glass filled Polyamide/ TPE
Harness	Kevlar blend webbing
Backplate	Glass and Carbon filled Nylon composite
Backpad	Flame retardant cross linked polyolefin closed cell foam covered in a Proban fabric
Cylinder Band	Kevlar blend webbing & Velcro
Strap Buckles	Glass filled polyamide
Cylinder	Steel or Composite
Cylinder Valve	Nickel Plated Brass
Demand Valve Casing	Glass filled Polyamide
Airline Belt Manifold	MP hose as above with brass fittings
Plastic Mounting Mouldings	Glass Filled Polyamide
WEIGHT / DIMENSIONS	
Single configuration (less cylinder)	2.6kg
Single configuration & facemask (less cylinder)	3.2kg
Length	630mm
Width	285mm
Depth (with 6.0 litre 200 bar cylinder)	215mm

SPECIFICATIONS

APPROVALS

EN137 Type 2	Open circuit self contained compressed air breathing apparatus
EN136	Full facemasks for respiratory protective devices
AS1716	Australian approval for respiratory protective equipment
MED	Marine Equipment Directive (Shipswheel)

MAJOR COMPONENTS - PROPAK-SIGMA

Tempest Demand Valve

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility. Components injection moulded from polyamide with rubber seals and diaphragms.

Peak flow performance:-	in excess of 1000 litres/minute
Bypass flow:-	150 litres/minute nominal
Static positive pressure:-	1.0 - 4.0 mbar

Reducing Valve

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve.

Valve body and cap machined from nickel plated brass with stainless steel spring and hose retainer U-clips. Cylinder connector to EN144-1 threads for use with 200 and 300 bar cylinder

OUTLET PRESSURE

200 bar inlet:-	5.5 to 9.5 bar
300 bar inlet:-	6.0 to 11.0 bar
Pressure relief valve protected:-	13.5 bar
Flow restrictor to gauge supply hose	<25 litres minute

Pressure Indicator & Warning Whistle

Bourdon tube type dial indicator
Heat and Impact resistant polycarbonate lens
Safety blow-out vent in rear of gauge
Accuracy:- +/- 10 bar between 40-300 bar

Hoses

Stainless steel swivel hose fittings

MEDIUM PRESSURE HOSE

Maximum working pressure	16 bar
Minimum burst pressure	80 bar

HIGH PRESSURE HOSE

Maximum working pressure	450 bar
Minimum burst pressure	800 bar