

PROPAK-FX

HIGH PERFORMANCE, RUGGED DEPENDABILITY, TRUSTED TECHNOLOGY



The ProPak-FX has been designed specifically to meet the demands of the Professional Fire Service offering an unequalled level of performance and user comfort through the adjustable backplate.

The entire ProPak range has been approved to EN137:2006 Type 2, incorporating the stringent Full Flame Engulfment Test, and to the 9th amendment of the MED meaning that it has the latest approval for the Marine industry.

PRODUCT HIGHLIGHTS

- EN137:2006 Type 2 MED Approved Breathing Apparatus
- Designed specifically for use by the Professional Fire Service
- Rigid backframe construction with adjustable backplate
- Easily removable pneumatics
- Simple to service and maintain

PROPAK-FX

SELF CONTAINED BREATHING APPARATUS



MAJOR COMPONENTS

Compact positive pressure demand valve featuring servo-assisted, tilting diaphragm mechanism with low inspiratory resistance and responsive dynamic performance, automatic first breath actuation and hands free bypass facility

REDUCING VALVE

First stage pressure reducing valve featuring non-adjustable, spring loaded piston mechanism and outlet supply protected by pressure relief valve

HOSES

Stainless steel swivel hose fittings
 Medium pressure hose
 High pressure hose
 Medium working pressure 16 bar
 Minimum burst pressure 80 bar
 Maximum working pressure 450 bar
 Minimum burst pressure 800 bar

PRESSURE INDICATOR & WARNING WHISTLE

Bourdon tube type dial indicator
 Heat and Impact resistant polycarbonate lens

COMMUNICATIONS

The Sabrecom2 is a radio communication interface designed for use with Scott Safety's range of positive pressure full facemasks. Fully integrated and ready to use the Sabrecom 2 is approved to EN136 class 3, meeting the stringent flame and radiant heat test requirements.

OPTIONS

The Scott Safety ProPak-FX can be specified in many configurations including Duo, Split Demand Valve Coupling (SDC), Y-Piece (Y2C) and attachments for Airline, which can be used for Rescue Second Man and Decontamination. Cylinder quick connect and fast fill options are also available.



Product Specifications

Weight

Single Configuration (less cylinder)	3.4kg
Single Configuration and facemask (less cylinder)	4.0kg

Dimensions

Length	630mm
Width	285mm
Depth (with a 6 litre 200 bar cylinder)	220mm

Ordering Information

Part Number	Description	Application
ProPak-FX	EN137 Approved, Type 2	Professional Fire Service



www.norrscope.com