

Laboratory Chamber Furnace - CWF

CWF 12/36

| | |
|--|------------------|
| Max temp (°C) | 1200 |
| Max continuous operating temp (°C) | 1100 |
| Volume (litres) | 36 |
| Heat-up time (mins) | 37 |
| Dimensions: Internal H x W x D (mm) | 250 x 320 x 450 |
| Dimensions: External H x W x D (mm) | 810 x 690 x 780 |
| Dimensions: External with door open H x W x D (mm) | 1105 x 690 x 780 |
| Temperature uniformity of ± 5°C within H x W x D (mm) | 170 x 240 x 357 |
| Max power (W) | 9000 |
| Holding power (W) | -- |
| Thermocouple type | R |
| Weight (kg) | 100 |

CWF 12/65

| | |
|--|------------------|
| Max temp (°C) | 1200 |
| Max continuous operating temp (°C) | 1100 |
| Volume (litres) | 65 |
| Heat-up time (mins) | 40 |
| Dimensions: Internal H x W x D (mm) | 278 x 388 x 595 |
| Dimensions: External H x W x D (mm) | 885 x 780 x 945 |
| Dimensions: External with door open H x W x D (mm) | 1245 x 780 x 945 |
| Temperature uniformity of ± 5°C within H x W x D (mm) | 178 x 288 x 455 |
| Max power (W) | 14000 |
| Holding power (W) | -- |
| Thermocouple type | R |
| Weight (kg) | 165 |